

**Ordering information**
**1** SSI **2** -L **3** **4** **5** - **6**
**1** Current Rating - 01,02,03,04,06,08,10,13,15


 13 ; 13A for UL, CUL approved, 10A for VDE, CQC approved  
 15 ; 15A for UL, CUL approved, 10A for VDE, CQC approved

**2** Schematic type

Standard (empty), B, D, E, F, H, J, K, M

**3** Components table

Refer components table

**Schematic type**
**Standard**


R:options Lg:options

\* please call for other's alternates

**4** Ground choke (options)

 G ; Lg=100uH  
 G1 ; Lg=6uH  
 G2 ; Lg=180uH

**5** Bleeder resistor (options)

R ; R=1M ohm; 1/4W min.

**6** Output terminal type

 Q ; fast-on(6.3mm)  
 S ; solder(4mm)  
 W ; with wire

**Insertion loss table**

(In 50ohm system according IEC/CISPR No.17)


Code	Rating	Comm. Mod(L-G)in MHz					Dist. Mod(L-Lin) MHz						
		15	5	1	5	10	30	15	5	1	5	10	30
Empty	1A	34	38	40	32	26	11	9	25	37	71	62	12
	2A	29	32	55	48	49	51	8	23	54	68	64	14
	3A	28	36	39	45	48	39	8	19	27	58	65	15
	4A	28	36	39	45	48	39	8	19	27	58	65	15
	6A	18	24	28	44	50	47	8	18	26	43	51	31
	8A	20	25	30	44	47	40	8	18	24	65	59	22
	10A	8	14	19	33	41	39	8	18	25	29	38	31
	13A	7	14	19	34	40	38	7	17	23	36	47	27
	15A	7	14	19	34	40	38	7	17	23	39	47	27
	B	1A	29	33	47	53	57	41	8	23	35	73	58
2A		28	37	44	52	56	41	8	19	27	74	59	17
3A		25	33	46	53	57	44	8	19	29	63	62	13
4A		20	24	26	27	25	15	8	18	24	58	57	21
6A		19	29	36	49	55	46	8	18	23	50	54	24
8A		20	24	26	27	25	15	8	18	24	58	57	21
10A		11	19	24	41	63	36	8	18	24	51	46	25
13A		8	15	21	37	46	36	7	17	23	39	48	27
15A		7	15	21	37	46	36	7	17	23	39	48	27

**Components table**

Code	Cx(uF)	Cy(pF)	Inductance L=mmH x 2 in Amps								Max. Leakage(mA)	Rating Volts	Hi-pot test Volts				
			1A	2A	3A	4A	6A	8A	15A	13A			15A	L-N-G	L-N		
Empty	0.1	2200	6.5	3.8	2.5	2.5	0.8	1.05	0.2	0.2	0.2	0.2	0.4	115/250	50/80	2250/DC	1450/DC
B	0.1	3300	3.7	2.7	1.8	1.3	0.8	1.05	0.3	0.2	0.2	0.25	0.5	115/250	50/80	2250/DC	1450/DC

\* please call for other's combinations

**Mechanical Dimension**

 unit: mm  
 inch

**SUGGESTED PANEL CUTOUT  
 (MOUNTING FROM FRONT)**  
 THICKNESS OF PANEL IS FROM  
 0.8mm To 1.6mm
