

Ordering information

① SSI ② -F ③ ④ ⑤ - ⑥

① Current Rating - 16,20A

16; 16A for VDE, CQC approved
20; 20A for UL, CUL approved

② Schematic type

A,C,G,I,LL,N

③ Components table

Refer components table

④ Ground choke (options)

G ; L_g=100uH
G1 ; L_g=6uH
G2 ; L_g=180uH
G3 ; L_g=400uH


⑤ Bleeder resistor (options)

R ; R=1M ohm; 1/4W min.

⑥ Output terminal type

Q ; fast-on(6.3mm)
S ; solder(4mm)
W ; with wire

Schematic type



R:options L_g:options

* please call for other's alternates

Components table

Code	Cx(uF)	Inductance L _m mH x 2 in Amps							
		1A	2A	3A	6A	8A	10A	15A	20A
A	0.1	X	X	X	X	X	X	X	0.5

* please call for other's combinations

Insertion loss table

(In 50ohm system according IEC/CISPR No.17)

Code	Rating	Comm. Mode(L-G)in MHz					Diff. Mode(L-L)in MHz						
		.15	.5	1	5	10	30	.15	.5	1	5	10	30
A	20A	16	21	22	24	25	20	8	18	25	42	43	30

* please call for other's combinations

Mechanical Dimension

unit: mm
inch

