



5 Watt Series

Wall Mount Type
USA / Japan / Taiwan / Europe / UK / Australia

ATS005T - W X X X □

O / P Voltage ← → U : US Plug / JP Plug
E : EU Plug
B : UK Plug
A : AU Plug

Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI
No Load Power Consumption Less Than 0.075W

Features :

- IEC/EN/UL 62368-1 & 60950-1
- 100-240VAC Universal Input
- Single Output to 5W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS005T-W033□	3.3V	1.50A	4.95W
ATS005T-W050□	5.0V	1.00A	5.00W
ATS005T-W051□	5.0V	1.50A	7.50W
ATS005T-W060□	5.9V	1.20A	7.08W
ATS005T-W075□	7.5V	1.00A	7.50W
ATS005T-W090□	9.0V	0.67A	6.03W
ATS005T-W120□	12.0V	0.60A	7.20W
ATS005T-W150□	15.0V	0.50A	7.50W
ATS005T-W180□	18.0V	0.33A	5.94W
ATS005T-W240□	24.0V	0.25A	6.00W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	0.19A Max.
Protection	Internal Primary Current Fuse
Configuration	U for US Plug / JP Plug E for EU Plug B for UK Plug A for AU Plug

Output

Load Regulation	±5% (Typical)
Ripple & Noise	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	22AWG / 20AWG / 18AWG
Ferrite Core	Yes

Safety Approvals

For USA - CB / UL / cUL / FCC / PSE / BSMI / LPS
For Europe & UK - CB / CE / GS / LPS

Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	0.25mA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI Certified
EMC Standards	EN55032 EN61000-3-2,3 EN55024
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332

Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimension	U - L 56 x W 28 x H 59 (mm) E - L 56 x W 28 x H 79 (mm) B - L 56 x W 49 x H 71 (mm) A - L 56 x W 41 x H 68 (mm)
Weight	U : 82g E : 96g B : 100g A : 94g (Ref.)

